



## Technical description

- Service water and steam boiler of 11lt., 3500/4500W in the 2 group version, 17lt., 4500/5400W in the 3 group version, with transversal exchangers and electric temperature control
- 550ml 700W coffee boilers powered by preheated water from the service boiler exchangers, independent electronic temperature control for each individual group
- Groups with thermosiphon heating by independent boilers
- Volumetric pump with balanced bypass
- Dual scale pressure gauge
- Filter holder with anti-scald handle
- Cool touch steam wands
- Lifting cup grilles
- 24Vdc solenoid valves with electronic management capable of detecting and signaling malfunctions or breakdowns
- Hot water mixer with two programmable doses from the menu
- 24V switching power supply
- Triac card for controlling the service boiler and coffee boiler resistances
- 72x54 mm color touch screen display: a main display for general programming of the machine functions, a display for each group used as a button panel for coffee dispensing and a display of the information of the relative group
- LED lights on the working area
- Sides molded in polyurethane with glossy two-tone paint and LED lighting
- Height-adjustable steel foot

Model	MIURA MULTIBOILER			MIURA MULTIBOILER	
Version	2 GROUPS			3 GROUPS	
Dimensions mm.	795x555x590h			1035x555x590h	
Steam boiler capacity	11 lt.			17 lt.	
Coffee boiler capacity	2 x 0.55 lt.			3 x 0.55 lt.	
Steam power	2400W	3500W	4500W	4500W	5400W
Coffee power	2 x 700W			3 x 700W	
Max Power	2400W*	3500W*	4500W*	4500W*	5400W*
* Maximum absorption with sequential heating activated (coffee heating priority)					
Power supply	110V-60hz	220/240V-50/60Hz 230/400V-50/60Hz		220/240V-50/60Hz 230/400V-50/60Hz	
Weight	67 kg			81 kg	
Colors					